





Miscellaneous Flashing

Unpainted Galvanized Ridge Roll Cap (29 ga.)	Description	Pack Qty.	Part No.
	10' x 9"	10	56070

Unpainted Flashing Angle (.0167")	Description	Pack Qty.	Part No.
	120° 10' x 4½" x 4½"	10	54450
	<ul style="list-style-type: none"> • Rust-free aluminum 120 degree angle, used where roof and walls meet. Angle helps weatherproof this area • Use for wall to roof weather-proofing junctions • Cap wood to prevent water damage • Longer length affords fewer seams 		

Unpainted Aluminum Rain Diverter (.020")	Description	Pack Qty.	Part No.
 	60" x 7½" x 2½"	10	54020
	<ul style="list-style-type: none"> • Use over doorways where no gutter is in place • Prevents roof runoff from waterfaling • Rust-free aluminum with hemmed edges for strength and safety 		

Kick-Out Diverter (29 ga.)	Description	Pack Qty.	Part No.
	Unpainted Galvanized Steel	12	KOGA
	White Steel	12	KOWH
	Black Steel	12	KOBK
	Bronze Steel	12	KOBZ
	<ul style="list-style-type: none"> • Meets the IRC 2009 code R905.2.8.3 that requires a 4" vertical Kickout Diverter Sidewall Flashing • Diverts roof drainage away from wall into gutter. Avoids a source of mold problems and foundation damage • Eliminates wall stains at roof line due to uncontrolled rainwater • Electro galvanized steel or powder coated finish to suit your application • Symmetrical construction can be used as Left or Right Diverter • Easy step instructions attached to every KOD flashing bottom face 		

Moisture Protection



Colors shown are for reference only. All thicknesses are inches unless otherwise noted. Tolerance is ± .002 inches.